

# BRAND-NEW CLEAR STYLE

Maintaining your car's quality like new forever



## JN-SHIELD

Automotive paint protection film

JN-SHIELD is a highly water-repellent, antifouling protection film that protects your valued car from dirt, scratches, and corrosion.





## Automotive paint protection film

JN-SHIELD is a urethane film protecting the painted surface of a car which is produced by utilizing the latest technologies from Japanese chemical manufacturers.

The film, which is manufactured under a rigorous quality management system, completely protects your valued car from color loss due to ultraviolet radiation, unexpected flying pebbles, or scratches.

---

### Features

---

#### XA0074

XA0074 and XA0157 are highly water-repellent, soil-resistant paint protection films that use a top coating with specialized antifouling performance.

With their highly elastic, fitting adhesive layer, the films are also characterized by their ease of cutting and processing.

#### XA0177

XA0177 is a thin paint protection film developed with the aim of solving problems such as the whitening and yellowing of headlights and the corrosion of imported cars' plated moldings.

Unlike thick ones, this film does not easily come off when the car is washed and is effective in preventing the easy occurrence of defects.

---

### Characteristic

---

#### XA0074 for the painted surfaces of cars

XA0074 has the highest grade of antifouling performance in the JN-SHIELD product lineup. It protects your valued car from not only abrasion and scratches but also scratches from flying pebbles.

Material: Polyurethane  
TPU thickness: 150 µm  
Adhesive capacity: 25N (24h)  
Contact angle: 103 (pure water)  
UV cut rate: 99%  
Size: 1,525 mm×15 m

#### XA0177 for headlights and plated moldings

XA0177 cuts ultraviolet radiation by 97-99%, so reducing the deterioration of headlights. It restores the transparency of headlights that have darkened and maintains it for a long period of time.

Material: Polyurethane  
TPU thickness: 100 µm  
Adhesive capacity: 26N (24h)  
Contact angle: 100 (pure water)  
UV cut rate: 97%  
Size: 762 mm×20 m



7114, Minamitamagakicho, Suzuka-shi, Mie-ken 513-0816 TEL.059-392-5152

For the specifications and other details of the products, as well as to make inquiries, visit:

<https://solatec.co.jp/>